

TYPE: Instikk	INV Mål		Spole diameter	Luft mengde [m³/h]	Virknings grad %	Standard byggelengde [mm] ca 40Pa	Alt Lengde ca 60-80Pa		Lengde rotordel [mm]
	Bredde	Høyde					X-del X1	X-del X2	
RX010	820	820	770	2 000	80,8	800		340	
RX015	865	865	815	2 500	78,6	800		340	
RX020	910	910	860	3 000	77,0	800		340	
RX030	960	960	910	3 500	76,1	900		340	
RX033	1055	1055	1005	4 000	77,9	900		340	
RX035	1150	1150	1100	4 500	79,5	900		340	
RX040	1200	1200	1150	5 200	78,5	1000		340	
RX045	1278	1278	1228	6 000	78,2	1000		360	
RX050	1360	1360	1310	7 000	77,7	1000		360	
RX055	1475	1475	1425	8 000	78,0	1200	1000	360	
RX060	1590	1590	1540	9 000	79,0	1200	1000	360	
RX065	1665	1665	1615	9 500	80,0	1200	1000	360	
RX070	1740	1740	1690	10 000	80,9	1200	1000	360	
RX080	1840	1840	1790	13 000	77,7	1400	1200	360	
RX085	1940	1940	1890	14 000	78,6	1400	1200	360	
RX090	2040	2040	1990	15 750	78,4	1400	1200	360	
RX093	2120	2120	2070	18 000	77,1	1600	1300	360	
RX095	2200	2200	2150	19 000	77,7	1600	1300	360	
RX100	2340	2340	2290	20 000	79,5	1600	1300	360	
RX105	2500	2500	2450	23 000	78,5	1600	1300	380	
RX110	2640	2640	2590	26 000	78,4	1800	1500	380	
RX115	2808	2808	2758	30 000	78,2	1800	1500	380	
RX120	2980	2980	2930	37 000	75,6	1900	1700	380	
RX125	3127	3127	3007	40 000	76,3	1900	1700	440	
RX128	3373	3373	3253	45 000	77,4	1900	1700	440	

